

WHAT IS CLAIMED IS:

1. An information transmission network system comprising:

5 a plurality of node units each accommodating at least one lower-tier terminal, and

service transmission lines and protection transmission lines interconnecting said node units;

wherein said node units comprise:

10 a normal operating means for transmitting information in the main traffic by setting a main traffic communication path in said service transmission lines and transmits information in the sub-traffic by setting a sub-traffic communication path, if necessary, in said protection transmission lines,

15 a failure detection means for detecting failure in said service transmission lines, and

20 a backup operating means for inserting a predetermined signal, when a failure has been detected by said detection means, at every exit to lower-tier terminals substantially connected to said protection transmission lines and then switches the main traffic communication path set in the failed service transmission lines to said protection transmission lines.

25 2. The information transmission network system according to claim 1, wherein the backup operating means in said node units inserts a first predetermined

09788593 022101

signal at the exit to lower-tier terminals where said sub-traffic communication path is set and inserts a second predetermined signal, which is different from said first predetermined signal, at the exit to lower-tier terminals where no sub-traffic communication path is set.

3. The information transmission network system according to claim 2, wherein the backup operating means in said node units inserts the AU-AIS signal (Administrative Unit-Alarm Indication Signal) as said first predetermined signal and the UNEQ (Unequipped) signal as said second signal, when said information transmission network system has a configuration conforming to SDH (Synchronous Digital Hierarchy).

4. A traffic control method for use in network systems having a plurality of node units each accommodating at least one lower-tier terminal and service transmission lines and protection transmission lines interconnecting said node units, comprising:

a step of detecting failure in said service transmission lines;

a step of normal operation that, when no failure is detected in said failure detection step, transmits information in the main traffic by setting a main traffic communication path in said service transmission lines and transmits information in the sub-traffic by setting a sub-traffic communication path, if necessary,

in said protection transmission lines;

a step of backup operation that, when a failure is detected in said failure detection step, inserts a predetermined signal at the exit to lower-tier

5 terminals substantially connected to said protection transmission lines; and

a step of switching the main traffic communication path set in the failed service transmission lines to said protection transmission lines, after said

10 predetermined signal has been inserted.

5. The traffic control method according to claim 4, wherein said step of inserting a predetermined signal comprises:

15 a step of checking the protection transmission lines corresponding to the service transmission lines where a failure has been detected in said failure detection step for any sub-traffic communication path; and

20 a step of inserting a predetermined signal that, when a sub-traffic communication path is detected in said failure detection step, inserts a first predetermined signal at the exit of the sub-traffic communication path to lower-tier terminals, and when no sub-traffic communication path is detected in said
25 failure detection step, inserts a second predetermined signal at the exit to lower-tier terminals substantially connected to said protection transmission lines.

00788593.022104

6. The traffic control method according to claim 5, wherein said steps of inserting a predetermined signal inserts the AU-AIS signal (Administrative Unit-Alarm Indication Signal) as said first predetermined signal and the UNEQ (Unequipped) signal as said second predetermined signal, when said information transmission network system has a configuration conforming to SDH (Synchronous Digital Hierarchy).

7. In node units for use in information transmission network systems that have a plurality of node units each accommodating at least one lower-tier terminal, connect node units with service transmission lines and protection transmission lines, during normal operations, carry main traffic information through a main traffic communication path set in said service transmission lines, and carry sub-traffic information through a sub-traffic communication path, if necessary, set in said protection transmission lines,

the node unit comprising:

a transmitted information exchange unit that transmits and receives information through a predetermined communication path selectively between said service transmission lines and protection transmission lines;

at least one interface unit for said lower-tier terminals that is each mounted in said at least one

09788593.022101

lower-tier terminal and transmits and receives information between the corresponding lower-tier terminals and said transmitted information exchange unit; and

5 a control unit that monitors said service transmission lines and protection transmission lines for failure, and, upon the detection of failure in said service transmission lines, terminates the communication path substantially connected to said protection transmission lines by making said interface unit for
10 lower-tier terminals send predetermined signals to lower-tier terminals and then makes said transmitted information exchange unit switch the main traffic communication path to the protection transmission lines.

15 8. The node units according to claim 7, wherein said control unit has:

 a sub-traffic communication path detection means for checking the protection transmission lines corresponding to the service transmission lines where a
20 failure has been detected in said failure detection step for any sub-traffic communication path; and

 a predetermined signals insertion means for making the interface unit for lower-tier terminals that serves as the exit of the corresponding path to lower-tier
25 terminals send a first predetermined signal to lower-tier terminals when a sub-traffic communication path is detected by said detection means, and for making the

interface unit for lower-tier terminals that serves as
the exit to lower-tier terminals substantially
connected to said protection transmission lines send a
second predetermined signal to lower-tier terminals
5 when no sub-traffic communication path is detected.

9. The node unit according to claim 8, wherein
said predetermined signal insertion means sends the
AU-AIS signal (Administrative Unit-Alarm Indication
Signal) as said first predetermined signal and the UNEQ
10 (Unequipped) signal as said second signal, when said
information transmission network system has a
configuration conforming to SDH (Synchronous Digital
Hierarchy).

09788593 022401